

FTB-202

Fiber Terminal Box

2 IN 2 OUT, Max 12 cores, Plastic



Overview

FTB-202 series fiber terminal box also called fiber cassette box is able to hold up to 12 cores of fibers. It is used as a termination point for the drop cable to connect with the patch cable in FTTH indoor application. It integrates fiber splicing, termination, storage, and cable connection in one solid protection box.

Features

- Dust-proof design with IP-45 Protection level.
- Integrated with splice cassette and cable management rods.
- Manage fibers in a reasonable fiber radius condition.
- Easy to maintain and extend the capacity.
- Suitable for fusion splice or mechanical splice.
- Embedded type surface, easy for installation and removal.
- 12 ports cable entrance for patch cable.

Application

- Widely used in FTTH access network.
- Telecommunication Networks
- CATV Networks
- Data communications Networks
- Local Area Networks

Technical Specifications

Parameter	Specifications
Optical fiber winding radius	≥40mm
Fiber length left in tray	≥1.6m
Fiber diameter	250um&900um
Fiber type	SM&MM
Operating temperature	-40 ~ +60 C
Connecting Adapter	SC & LC
Color	White
Material	PC+ABS
Weight	0.2KG

Order Information

Model	Dimension	Max.Capacity	Note
FTB-202	150*104*30mm	12	Wall



For further information, please visit our website <https://www.aoatech.com>

All rights are reserved by AOA Technology Co.,Ltd. AOA reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.