


ODF-E-48

Optical Distribution Frame

3U optical distribution frame 48 Cores



Overview

Fiber Management Tray also called ODF Distribution Box, Integrated Splicing and Distribution ODF. It is mainly used for cable inlet, grounding and fixing and the splicing between the terminal end and pigtail. Users can select unit or ring flange amount according to their practical needs.


Welding & distribution module in integration: Plastic structure, easy for installation of inlay, convenient to expand capacity, obliquity of adapter is 30°, which ensure the bend radius of patch cord and avoid laser burning eyes. Kinds of splicing and distribution mark, easy to make fusion and distribution record.

Features

- 19" standard mounting design with static electric plastic sprayed, nice appearance;
- Can be used for ribbon & bunch fiber cables;
- The trays will accept all types of adapters FC/SC/ST/LC(LC only can be duplex);
- Pre-installed trays with pigtails and adapters are available;
- Hinged and removable metal cover door;
- Cable fixation and grounding function;
- It is flexible for installation and convenient for operation and maintenance.

Application

- Widely used in FTTH access network.
- Telecommunication Networks
- CATV Networks
- Data communications Networks
- Local Area Networks




Technical Specifications

Item	Specifications
Atmosphere pressure	70 Kpa~106Kpa
Insertion loss	≤0.3dB
Return loss	PC≥40 dB UPC≥50dB APC≥60dB
Insulating resistance between the box and the earthing device	1000MΩ/500VDC
Voltage-resistance between the box and the earthing device	Under the effect of 3kv/DC/1min, non-puncture, and no arc-over.
Working temperature	-5°C - +40°C
Environmental temperature	-25°C - +55°C
Relative humidity	≤85% (when the temperature is below 30°C)

Order Information

Type	Dimension (mm)	Inner carton dimension (mm)	Inner carton weight (KG)	Outer carton dimension (mm)	Outer carton weight (KG)	No of units per carton (PCS)
ODF-E-48	480×260×133 (3U)	475*335*170	6.5	500*350*540	22	3

Accessories



For further information, please visit our website <https://www.aoatech.com>

All rights are reserved by AOA Technology Co.,Ltd. AOA reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.