

IMS5200

Industrial Managed 10G Switch

L2+ managed, 8/16/24x10/100/1000Base-T + 4x10G SFP




Overview

IMS5200 Industrial L2+ Managed Switch adopts the store-forward architecture, fan-less, and energy-saving design, providing 8/16/24-port 10/100/1000M RJ45 port and 4x 10G SFP+ Uplink port. Full-series design with protection against lightning, anti-static, and operate in -40°C~85°C for harsh environments; such as industrial automation, public security, power system, intelligent transportation systems (ITS), shipping, mining, and water conservancy fields.

Features

- Support static routing, RIPv1/v2, OSPFv2, VRRP, BGP dynamic routing and policy routing
- Support STP/RSTP/MSTP, ERPS Fast ring protocol
- Supports flow control, loop protection, link aggregation, storm suppression, mirroring, and DDM
- Support IEEE802.1Q VLAN, QinQ VLAN, protocol VLAN, Voice VLAN, Private VLAN, GVRP
- Supports SP, WRR, SP+WRR scheduling, ensure priority flow forwarding
- Support IGMP Snooping, MLD Snooping, suit for HD Video surveillance and video conference
- Support Web, CLI, SNMP(V1/V2/V3), Telnet management
- Support HTTPS、SSH encryption, making management more secure
- Supports RMON, system logs, and traffic statistics to facilitate network optimization
- Supports LLDP, making network maintenance simple
- Support DHCP Snooping, Qos, ACL
- Supports 802.1X authentication and MAC address filtering, ensures the legitimacy of access users
- Supports CPU monitoring, Ping detection, Traceroute detection
- Support PoE Management
- Providing 8/16/24-port gigabit access and 4x 10G uplink products
- Adopt Industrial Level-4 design, support EFT/ESD/Surge projection
- Working Temperature -40~85°C
- 12~58Vdc or 100~240Vac dual input
- Complete LED indicators to identify the working status quickly
- IP40 anti-oxidation aluminum alloy, weight lighter and head release rapidly

Product List

Model	Description
 IMS5200-8T4X	Port: 8x 10/100/1000M RJ45, 4x 10G SFP+ Switch Capacity: 128G Packet forwarding Rate: 71.4Mpps MAC address: 16k Buffer: 12M Power Input: 12~58Vdc dual input Working Temperature: -40~85°C Size: 170x120x60mm
 IMS5200-8P4X	Port: 8x 10/100/1000M PoE, 4x 10G SFP+ Switch Capacity: 128G Packet forwarding Rate: 71.4Mpps MAC address: 16k Buffer: 12M Power Input: 44~58Vdc dual input Working Temperature: -40~85°C Size: 170x120x60mm
 IMS5200-8B4X	Port: 8x 10/100/1000M PoE(bt), 4x 10G SFP+ Switch Capacity: 128G Packet forwarding Rate: 71.4Mpps MAC address: 16k Buffer: 12M Power Input: 44~58Vdc dual input Working Temperature: -40~85°C Size: 170x120x60mm
 IMS5200-8T2S4X	Port: 8x 10/100/1000M RJ45, 2x 1G SFP, 4x 10G SFP+ Switch Capacity: 128G Packet forwarding Rate: 74.4Mpps MAC address: 16k Buffer: 12M Power Input: 12~58Vdc dual input Working Temperature: -40~85°C Size: 170x120x60mm
 IMS5200-8P2S4X	Port: 8x 10/100/1000M PoE, 2x 1G SFP, 4x 10G SFP+ Switch Capacity: 128G Packet forwarding Rate: 74.4Mpps MAC address: 16k Buffer: 12M Power Input: 44~58Vdc dual input Working Temperature: -40~85°C Size: 170x120x60mm

 IMS5200-8B2S4X	Port: 8x 10/100/1000M PoE(bt), 2x 1G SFP, 4x 10G SFP+ Switch Capacity: 128G Packet forwarding Rate: 74.4Mpps MAC address: 16k Buffer: 12M Power Input: 44~58Vdc dual input Working Temperature: -40~85°C Size: 170x120x60mm
 IMS5200-24T4X	Port: 24x 10/100/1000M RJ45, 4x 10G SFP+ Switch Capacity: 128G Packet forwarding Rate: 95.2Mpps MAC address: 16k Buffer: 12M Power Input: 12~58Vdc dual input Working Temperature: -40~85°C Size: 440x270x43.6mm
 IMS5200-16T8C4X	Port: 16x 10/100/1000M RJ45, 8x 1G Combo, 4x 10G SFP+ Switch Capacity: 128G Packet forwarding Rate: 95.2Mpps MAC address: 16k Buffer: 12M Power Input: 100~240Vac dual input Working Temperature: -40~85°C Size: 440x270x43.6mm
 IMS5200-16P8C4X	Port: 16x 10/100/1000M PoE, 8x 1G Combo, 4x 10G SFP+ Switch Capacity: 128G Packet forwarding Rate: 95.2Mpps MAC address: 16k Buffer: 12M Power Input: 100~240Vac, AC input 400/280W optional Working Temperature: -30~70°C Size: 440x270x43.6mm
 IMS5200-16S8C4X	Port: 16x 1G SFP, 8x 1G Combo, 4x 10G SFP+ Switch Capacity: 128G Packet forwarding Rate: 95.2Mpps MAC address: 16k Buffer: 12M Power Input: 100~240Vac dual input Working Temperature: -40~85°C Size: 440x270x43.6mm

Technical Specifications

Model	14-port Din Rail	28-port Rack-mounted
Performance		
Standards	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.2an, IEEE802.3ae IEEE802.3z, IEEE802.3x, IEEE802.1Q VLAN, IEEE802.1d, IEEE802.1w, IEEE802.1s	
Forwarding mode	Store and Forward	
Switch Capacity	128Gbps/non-blocking	
Packet forwarding Rate	Refer to the product list	
MAC Address	16k	
Buffer	12M	
Jumbo Frame	10k	
Ports		
Copper port	10/100/1000M RJ45 Cat5/cat6 100M	
1G Fiber Port	1000/100M SFP Slot OM1/OM2 550m, OS1/OS2 up to 120km	
10G Fiber Port	10G SFP+ Slot OM3 300m, OS1/OS2 up to 120km	
Console	RS232 (RJ45)	
PoE		
Standard	IEEE802.3af/at	
Pin Assignment	1/2+, 3/6-	
PoE Budget	≤30W	
Electrical characteristics		
Power Input	12~58Vdc, 44~58Vdc(PoE)	100~240Vac 50/60Hz dual input
Power Consumption	Refer to spec	
Power connector	Terminal block	
Reverse polarity	support	/
Physical characteristics		
Housing	Metal, IP40 protection	
Installation	DIN rail, Wall-mounted (Optional)	Rack-mounted
Heat Release	Natural	
Size	170x120x60mm	440x270x43.6mm
Environment		
Working Temperature	-40℃ ~ 85℃	

Storage temperature	-40°C ~ 85°C
Relative Humidity	5%-95% (no condensation)
Certification	
Safety	EN62368
EMC	EN55032 Class A, FCC part 15 Subpart B Class A EN 61000-3-2 Class A EN 61000-3-3 Class A EN 61000-4-2 Level 4 Contact: 8kV ,Air: +15kV EN 61000-4-3 Level 4 EN 61000-4-4 Level 4 Power: ±4kV; Signal: ±2kV EN61000-4-5 Power: 6kV, Copper: Comm 4kV, diff. 2kV EN 61000-4-6 Level 3 EN 61000-4-8 Level 4 30A/m EN 61000-4-11 Voltage dip/interruption
RoHS	RoHS 2.0
Reliability	
Shock	IEC 60068-2-27
Free fall	IEC 60068-2-32
Vibration	IEC 60068-2-6

Software Feature

L2 Feature	
Port Feature	IEEE802.3x Flow control , Interface counters, Storm control, DDM
Port Isolate	support
Link Aggregation	Static aggregation, Dynamic aggregation (LACP)
Port Mirror	Port-based mirror
Spanning Tree	STP, RSTP, MSTP
VLAN	4094 VLAN, Port-Base VLAN
MAC Address	IEEE 802.1q, MAC 16K Static mac-address, Dynamic mac-address, mac-address Filtering , IVL mode
QinQ	Port-based QinQ, Vlan-based QinQ, Flow-Based QinQ, 1:1 VLAN Mapping
LLDP	LLDP, LLDP-MED
ERPS(G.8032)	Single-ring, sub-ring, multi-ring

Multicast	IGMP V1 Snooping, IGMP V2 Snooping, IGMP V3 Snooping, IGMP Fast Leave, Static Multicast Entry
L3 Feature	
ARP	Static ARP, Dynamic ARP, ARP proxy
Routing strategy	IP Prefix-list, IP ACL, Route-Map
IPv4	Static route, Support Blackhole route
Security Features	
ACL	IP Standard ACL, MAC extend ACL, IP extendACL
QoS	QoS Class, Remarking SP, WRR,SP+WR queue scheduling Ingress Port-based Rate-limit Egress Port-based Rate-limit Policy-based QoS
Dot1x	Port Access Control, Mac-address Access Control, RADIUS Server
Management Feature	
User management	password protection
SNMP	SNMP v1/v2c/v3
RMON	Statistics Group, History Group, Alarm Group, Events Group
Web Management	Web, support HTTP V1.1
Firmware Upgrade	support
Syslog/Debug	support
IPv4/IPv6	support
PoE Management	support 802.3af/at, PoE enable/disable, watchdog, info check
Diagnosis	ping(ipv4), ping(ipv6), Trace route(ipv4), Trace route(ipv6)
Application	
NTP	NTP Client
TFTP	TFTP Client
Telnet	Telnet Server, Telnet Client
DHCP	DHCPv4 Snooping (Trust Port) DHCPv4 Client, DHCPv6 Client, DHCPv4 Server, DHCPv6 Server

Order Information

Model No.	Description
IMS5200-8T4X	L2+, 8x 10/100/1000M RJ45, 4x 10G SFP+
IMS5200-8P4X	L2+, 8x 10/100/1000M PoE, 4x 10G SFP+
IMS5200-8B4X	L2+, 8x 10/100/1000M PoE(bt), 4x 10G SFP+
IMS5200-8T2S4X	L2+, 8x 10/100/1000M RJ45, 2x 1G SFP, 4x 10G SFP+
IMS5200-8P2S4X	L2+, 8x 10/100/1000M PoE, 2x 1G SFP, 4x 10G SFP+
IMS5200-8B2S4X	L2+, 8x 10/100/1000M PoE(bt), 2x1G SFP, 4x 10G SFP+
IMS5200-24T4X-2A	L2+, 24x 10/100/1000M RJ45, 4x 10G SFP+, Dual AC input
IMS5200-16T8C4X-2A	L2+, 16x 10/100/1000M RJ45, 8x 1G Combo, 4x 10G SFP+, Dual AC input
IMS5200-16S8C4X-2A	L2+, 16x 1G SFP, 8x 1G combo, 4x 10G SFP+, Dual AC input
IMS5200-16P8C4X-AC	L2+, 16x 10/100/1000M PoE, 8x 1G Combo, 4x 10G SFP+, AC input

Related Products

SFP modules

Model No.	Description
SFP-M1285L-05I	SFP 1.25G MM 850nm LC 550m DDM, Industrial Grade
SFP-S1213L-20I	SFP 1.25G SM 1310nm LC 20km DDM, Industrial Grade
SFP-B1235L-20I	SFP 1.25G SM TX1310/RX1550nm LC 20km DDM, Industrial Grade
SFP-B1253L-20I	SFP 1.25G SM TX1550/RX1310nm LC 20km DDM, Industrial Grade
SFP-M1085L-03I	SFP+ 10G MM 850nm LC 300m DDM, Industrial Grade
SFP-S1013L-20I	SFP+ 10G SM 1310nm LC 20km DDM, Industrial Grade
SFP-B1023L-20I	SFP+ 10G SM TX1270/RX1330nm LC 20km DDM, Industrial Grade
SFP-B1032L-20I	SFP+ 10G SM TX1330/RX1270nm LC 20km DDM, Industrial Grade
Notes: 40/60/80km available	

DIN rail Power Supply

Model No.	Description
HDR-15-24	DIN rail 15W, 85~264Vac input, 24Vdc 0.63A output
HDR-30-24	DIN rail 36W, 85~264Vac input, 24Vdc 1.5A output
HDR-60-24	DIN rail 60W, 85~264Vac input, 24Vdc 2.5A output
NDR-75-48	DIN rail 75W, 90~264Vac input, 48Vdc 1.6A output
NDR-120-48	DIN rail 120W, 90~264Vac input, 48Vdc 2.5A output
NDR-240-48	DIN rail 240W, 90~264Vac input, 48Vdc 5A output
NDR-480-48	DIN rail 480W, 90~264Vac input, 48Vdc 10A output

Installation Kits

Model No.	Description
 TK12	Wall-mounted kit, 118*18*16mm, ϕ 3.5mm L=12mm
 A01	Side DIN rail kit, 84*81.5*8.5mm, ϕ 3.5mm L=6mm
 CK01	Rack-mounted bracket, 483*215*130mm



For further information, please visit our website <https://www.aoatech.com>

All rights are reserved by AOA Technology Co.,Ltd. AOA reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.